

PXIS-3320

15-Slot 6U PXI/CompactPCI Chassis with 500 W Hot-Swappable Power Supply

Features

- Supports 6U PXI and CompactPCI modules
- PXI specifications Rev. 2.2 compliant
- Provides one system slot and 14 PXI/CompactPCI peripheral slots
- Dual hot-swappable 250 W CompactPCI power supply with universal AC input
- Filtered, forced air-cooling architecture
- Magnetic circuit breaker protection for AC input
- Temperature, voltage, and fan monitoring LEDs
- Optional 1000 W power supply

Introduction

The ADLINK PXIS-3320 is a 19" 6U PXI chassis comes with one system slot and 14 peripheral slots that flexibly supports PXI and CompactPCI modules. Compliant with the PXI specifications Rev. 2.2, the PXIS-3320 highlights a star trigger, PXI trigger bus, 10 MHz reference clock, and PXI local bus to facilitate synchronization among multiple peripheral modules. The PXIS-3320 series is equipped with two hot-swappable, industrial-grade 250 W power supply units and LEDs that tell the status of power, temperature, and system fans. In addition, two fan decks of PXIS-3320, which generate total 482 CFM air flow, provide the ultimate thermal stability. For applications requiring multiple, multi-standard modules, and robust design, insist on ADLINK PXIS-3320.

Specifications

Power Supply

- Form factor: PICMG 2.11 compliant CompactPCI power module
- AC input: 100 to 240 V_{AC}, 50 Hz to 60 Hz
- DC output for each power module: 250 W

V _{DC}	Minimum	Typical	Maximum
+5 V	2.0 A	25.0 A	33.0 A
+12 V	0.0 A	5.0 A	5.5 A
+3.3 V	0.0 A	18.0 A	33.0 A
-12 V	0.0 A	0.5 A	1.0 A

Cooling

- Fans for intake: Five 80 mm x 80 mm x 25 mm, dual ball-bearing fans, 48.2 CFM/each
- Fans for ventilation: Five 80 mm x 80 mm x 25 mm, dual ball-bearing fans, 48.2 CFM/each

Physical

- Dimension: 484 mm x 398 mm x 295 mm (W x H x D, without handles)
- Weight: 23 kg

Operating Environment

- Ambient temperature: 0°C to 45°C
- Relative humidity: 10% to 90%, non-condensing

Storage Environment

- Ambient temperature: -20°C to 70°C
- Relative humidity: 5% to 95%, non-condensing

Shock and Vibration

- Shock: 15 G_{peak-to-peak}, 11 ms duration
- Random Vibration
 - Operating: 5 Hz to 500 Hz, 0.5 GRMS, each axis
 - Non-operating: 5 Hz to 500 Hz, 1.88 GRMS, each axis

Recommended System Controller

- cPCI-6840
- cPCI-6910

Ordering Information

- **PXIS-3320**
15-Slot 6U PXI/CompactPCI Chassis with 500 W Hot-swappable Power Supply
- **PXIS-3320/1000W**
15-Slot 6U PXI/CompactPCI Chassis with 1000 W Hot-swappable Power Supply



PXIS-3320 Front



PXIS-3320 Back



Optional 1,000 W Power Supply

1 Software Solutions

2 PXI/CompactPCI Platforms

3 Modular Instrument

4 PXI/CompactPCI Modules

5 Bus Interface

6 GPIB Interface

7 PCI/PCI Express® DAQ Cards

8 PCI/PCI Express® DIO Cards

9 PC/104-Plus Modules

10 ISA DAS/DIO Cards

11 System Product

12 Wiring Termination Boards

13 Motion, HSL, Vision, COM & GEME

14 Remote I/O Modules

15 Industrial Computers