

Industrial Class Power Supply

Industrial Mini-Redundant AC Power Supply



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-930RAXA	300W	18A	25A	16A	0.5A	0.5A	2.0A	ATX12	90-264AC full range	UL/CSA/TUV
APS-946XAR	460W	25A	25A	30A	--	0.8A	2.0A	EPS12	90-264AC full range	UL/CSA/TUV

■ Dimensions: 185 x 150 x 86 (mm)

Industrial Dual Redundant AC Power Supply



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-6300F	300W	25A	20-36A	17A	0.8A	0.8A	2A	ATX	Input voltage: 90-264AC full Range manual switch, Frequency: 47Hz-63Hz	UL/CSA/TUV
APS-6400F	400W	25A	36A	17A	0.8A	0.8A	2A	ATX		UL/CSA/TUV

■ Dimensions: 187 x 167 x 183 (mm)

Industrial AC Power Supply PS/2 Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-935XA-ST	350W	30A	40A	18A	0.5A	1A	2A	ATX12	90-264VAC full range	UL/CSA/TUV
APS-940XA-ATX12	400W	25A	35A	30A	0.8A	1A	2A	ATX12	90-240VAC full range	UL/CSA/TUV
APS-940XA-ST	400W	30A	40A	18A	0.5A	1A	2A	ATX12	90-264VAC full range	UL/CSA/TUV
APS-946XA-EPS12	460W	30A	40A	32A	0.8A	1A	2A	EPS12	90-264VAC full range	UL/CSA/TUV

■ Dimensions: Standard PS/2 form factor, 140 x 150 x 86 (mm)

Industrial DC-DC Power Supply PS/2 Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	DC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-930/48X	300W	15A	30A	15A	2A	1.2A	1.2A	ATX	-40-57VDC	UL/CUL/TUV
APS-930/24	300W	15A	30A	15A	2A	2A	1.2A	AT	19-32VDC	UL/CSA/TUV

■ Dimensions: 150 x 140 x 86.2 (mm)

Industrial AC Power Supply 1U Form Factor



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-9125XA-ST	250W	17A	20A	18A	--	0.5A	2A	ATX12	90-264AC full range	UL/CSA/TUV
APS-9130XU	300W	20A	24A	20A	0.5A	0.5A	1.5A	ATX12	90-264AC full range	UL/CSA/TUV

■ Dimensions: 205 x 100 x 40.5 (mm)

Industrial Open Frame AC Power Supply for 1U Chassis



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-912XA	120W	12A	14A	6A	--	1A	0.75A	ATX ^(note1)	90-260VAC	UL/CSA/TUV
APS-908U	80W	--	6A	3.5A	0.5A	0.5A	--	AT ^(note1)	85-264VAC	UL/CSA/TUV

Note1: with optional designate cable

Industrial Flex ATX AC Power Supply for 1U Chassis



Model Name	Watt (Typical)	Maximum DC Output Current						Current Type	AC Voltage Input Range	Certificate
		+3.3V	+5V	+12V	-5V	-12V	+5Vsb			
APS-915FXM-ST	150W	10A	14A	2.1A	--	0.15A	1A	ATX	90-264VAC	UL/CUL/TUV

■ Dimension: 150 x 81.5 x 40.6 (mm)