

# Accessories

## LGA775 1U CPU Cooler

### Specification

- Height: 28mm
- Fan Speed: 5,500rpm
- Material: Copper
- Capability: 82W TDP max.
- Backplate included

### Ordering Information

- 32-20065-0000 (RoHS)



## LGA775 Copper-Core Cooler

### Specification

- Height: 62mm
- Fan Speed: 4,500rpm
- Material: Aluminum + Copper
- Backplate included

### Ordering Information

- 32-20086-0000 (RoHS)



## Socket-M 1U CPU Cooler

### Specification

- Height: 22mm
- Fan Speed: 5,500rpm
- Material: Copper
- Backplate included

### Ordering Information

- 32-20072-0000 (RoHS)



## LGA1156 Cooler

### Specification

- Height: 65mm
- Fan Speed: 2,700rpm
- Material: Aluminum
- Backplate included



## ATX12V Converter Cable

### Specification

- 4P to 2 x 2P cable

### Ordering Information

- 30-00006-0000 (RoHS)



## HDD Holder for 3.5" to 2.5" Kit

### Specification

- Supports two 2.5" storage

### Ordering Information

- 91-95056-000E (RoHS)



## IDE Cable - 70/90CM

### Specification

- ATA-100 IDE flat cable
- Length: 70/90 cm

### Ordering Information

- 30-10058-1000 70cm (RoHS)
- 30-10058-0010 90cm (RoHS)



## Slim SATA DVD-ROM Adapter Cable

### Ordering Information

- 30-20281-0000 (RoHS)



## COM Cable

### Specification

- Com cable with bracket
- Length: 23cm

### Ordering Information

- 30-25004-0000 (RoHS)



## USB 2.0 Cable

### Specification

- 2-port USB 2.0 cable with bracket

### Ordering Information

- 30-25010-1000 (RoHS)



## Audio Cable for NuPRO-852

### Specification

- Length: 210mm

### Ordering Information

- 92-99033-0010 (RoHS)



## Slim Type Optical Drive Adapter

### Specification

- Slim type optical drive to 40P IDE adapter

### Ordering Information

- 92-49006-001 (RoHS)



# PCIe Mini Card & Audio Cards

## mPCIe-8770

### PCIe 2D VGA Display Card

- PCIe VGA Controller XGI™ Volari™ Z11
- PCI Express Spec. compliant
- High Performance 2D Accelerator
- Supports 230 MHz pixel clock
- Supports 4:3 resolution up to 1600x1200, 256/32K/64K/16M colors (70Hz NJ)
- Driver support: Windows® 2000/XP/Vista/Vista-64, Fedora™ 10, RHEL™ 5



## DB-Audio2

### High Definition Audio Daughter Board with Line-in, Line-out and Mic-in

- Realtek ALC262 High Definition Audio codec
- Three jacks: line-in, line-out and mic-in
- 5x2 pin header for cable connection to external audio header on SBC
- 4-pin header interface for CD audio output



## DB-AC97S

### AC'97 Audio Daughter Board with Line-in, Line-out and Mic-in

- Realtek ALC200 AC'97 audio codec
- AC'97 interface with 10-pin header and fl at cable
- Three jacks: line-in, line-out and mic-in
- 4-pin header interface for CD audio output

