

aTCA-81414PD

14U 14-slot Dual-Star 40G AdvancedTCA® Shelf

Features

- 19" Rackmount, 14U height, 470mm depth
- 14-slot dual-star topology Fabric Interface
- 14-slot standard Rear Transition Module
- Dual-bussed IPMB
- Hot-swappable IPMC controlled fan trays
- Two shelf management controller slots
- Four-48 V DC power entry modules



Specifications

Mechanical

19" Rackmount, 14U height, 470mm depth

Specification

Fits inside a 600 mm deep cabinet (include cable bend area)

Supports 14-slot standard AdvancedTCA® blades and RTMs

Shelf Manager

Dual-hot-swappable Pigeon Point Systems ShMM-700 based ShMCs

Active/Standby mode for high availability applications

Supports multiple management interfaces:

- Remote Management Control Protocol (RMCP)

- Command Line Interface (CLI)

- 10/100BASE-T Fast Ethernet ports and one serial console

Cooling System

Hot-swappable IPMC controlled fan trays

Easily removable replaceable air filter

Backplane

Dual-Star topology Base Interface

Dual-Star topology Fabric Interface

Update channels for active/standby synchronization

Dual-bussed IPMB

Power Input

-40V DC to -75V DC

Nominal -48 V DC/-60 V DC

Four redundant power entry modules

Input nominal current 48V@200A (9600W)

Weight: 28 kg

Operating Temp.

+5°C to +40°C (long term)

-5°C to +55°C (short term)

Storage Temp.

-40°C to +70°C

Humidity

5% to 85%, non-condensing

Dimensions: 483 x 620 x 470mm (W x H x D)

Compliance: PICMG 3.0 Rev. 3.0 compatible

Target Certifications: FCC, CE, UL

Ordering Information

Shelves

- **aTCA-81414PD/DS40AA**

14U 14-slot Rackmount AdvancedTCA® Shelf, Dual-Star Fabric

Topology, Dual-bussed IPMI Bus

2 PPS ShMM-700 based ShMCs

ShMC (Optional)

- **aTCA-8AP/ShMC700**

Pigeon Point Systems ShMM-700 based ShMC

Dimensions

