

# RK-200I

2U Wall-mount/Tower Embedded Mini-ITX Chassis with One Dual Expansion Slot

Preliminary



## Features

- Supports one dual slot expansion card(Low Profile)
- Reserved for 2 USB, 2 COM, and 2 antenna punchouts.
- One 3.5" drive bay and one 2.5" drive bay. (Compatible for three 2.5" drive bays)
- 8cm two ball bearing PWM fan ( 42.5 CFM)
- Support both Flex ATX power supply & AC-DC power adaptor

## Ordering Information

Model Number	Color	Description
RK-200I	Black	2U Wall-mount/Tower Embedded Mini-ITX Chassis with One Dual Expansion Slot

## Power Supply Options

Model Number	Watt	Output (Max.)					
		Input Range	+3.3 V	+5 V	+12V	-12 V	+5 Vsb
FSP300-50FCB	300W	Universal	12 A	14 A	25 A	0.3 A	3 A
FSP500-50FDB	500W	Universal	14 A	16 A	41 A	0.3 A	3 A

## Specifications

Dimensions	10.23 in x 3.46 in x 9.45 in (260 mm x 88 mm x 240 mm) (W x H x D)
Drive Bays	One 3.5" drive bay and one 2.5" drive bay. (Compatible for three 2.5" drive bay)
Color	Black
Cooling Fans	In: one 80mm x 80mm x 25mm two ball bearing PWM fan ( 42.5 CFM)
Front Panel	LEDs: HDD active and system power System reset button and ATX power button Two USB type A connectors
Motherboard	Mini-ITX industrial motherboard
Power Supply	PS2 form factor Flex ATX power supply or AC-DC power adaptor
Carton Size	14.7 in x 7.87 in x 14.17 in (375 mm x 200 mm x 360 mm) (W x H x D)
Weight	2.65 kg ( 2.205 lbs)