

MLB-3100 Medical Box PC

Medical box PC with the 12th/13th/14th Gen Intel® Core™ i3/i5/i7/i9 in LGA1700 Socket, supporting MXM GPU module and Thunderbolt™ 4 (only for 12th Gen Intel® Core™ processors)

Compliant with IEC 60601-1 / IEC 60601-1-2



Features

- ADLINK MXM graphics module support (type A/B, up to 120W TDP based on power supply)
- 12th/13th/14th Gen Intel® Core™ i3/i5/i7/i9, Celeron® processor
- Dual SODIMM for up to 64GB DDR5 non-ECC memory (depending on CPU)
- 1x HDMI 2.0, 5x DisplayPort (1 from CPU, 4 from MXM)
- 1x M.2 E-key supporting 1630 or 2230 for Wi-Fi/Bluetooth module, 1x M.2 M-key supporting 2242 or 2280 for SATA/PCIe storage module, 1x M.2 M-key supporting 2242 or 2280 for NVMe & frame grabber
- Reliable Molex 24V DC-in connector
- 2x 2.5GbE Intel® I225-LM Ethernet Controller

Software Support

- Win 10/Win 11 IoT Enterprise
- Ubuntu 24.04

Ordering Information

- MLB-3100-i5-12500E/M16GB/512G
- MLB-3100-i7-12700E/M16GB/1TB

Accessories


- Adaptor
Medical 450W, 24 V / 18.75 A
- Screws package
3x M3 screws for M.2, 8x M3 screws for HDD try,
2x M2 screws for MXM card

Optional Accessories

- MXM cooler for A1000/A2000 kit: 91-95346-1010
- MXM cooler for A4500 kit: 91-95346-300E
- MXM cooler for RTX3000:32-20823-1100-A0
- Wall Mount Bracket 34-34546-0100-A0 2pcs
- Wi-Fi Kit Intel® AX210: 91-95333-200E

Dimensions

Unit: mm



Specifications

Model	MLB-3100		
MXM Support	EGX-MXM-A1000	EGX-MXM-A2000	EGX-MXM-A4500
Processor	Intel® Core™ i9-12900E, 5.0GHz, 14M Cache, 65W TDP, LGA1700, DDR5 4800MHz support Intel® Core™ i7-12700E, 3.6GHz, 12M Cache, 65W TDP, LGA1700, DDR5 4800MHz support Intel® Core™ i5-12500E, 3.0GHz, 7.5M Cache, 65W TDP, LGA1700, DDR5 4800MHz support Intel® Core™ i3-12100E, 3.2GHz, 5M Cache, 60W TDP, LGA1700, DDR5 4800MHz support		
Chipset	Intel® Q670E Chipset		
Memory	Non-ECC DDR5 4800MHz, 2x SO-DIMM, up to 64GB		
I/O Interfaces			
Display	1x HDMI 2.0, 5x DisplayPort (1 from CPU, 4 from MXM)		
Ethernet	2x 2.5GbE (Intel® I225-LM)		
Serial Ports	1x RS-232/422/485, 1x RS-232		
USB	[Front] 1x USB 3.2 Gen 2 Type A [Rear] 2x USB 3.2 Gen 2 Type A, 4x USB 3.2 Gen 1 Type A, 1x USB 3.2 Gen 1 Type C		
M.2	1x M.2 E-key supporting 1630 or 2230 for Wi-Fi/BT module, 1x M.2 M-key supporting 2242 or 2280 for PCIe/SATA for storage, 1x M.2 M-key supporting 2242 or 2280 for PCIe Gen 4 x4 for NVMe & frame grabber		
Digital IO	1x DI/DO with 4 in, 4out		
Audio	Default: Mic in & line out Option: L/R speaker-out (2W + 2W), Mic-in		
TPM 2.0	Default: TPM, optional w/o TPM		
Storage			
SATA/PCIe	2x 2.5" SATA 6Gb/s external drive bays 1x M.2 2242/2280 M key support SATA/PCIe gen 3 x3 to support storge 1x M.2 2242/2280 M key support PCIe gen 4 x4 to support		
Mechanical			
Dimensions	280 x 198 x 98 mm (W x D x H, without foot pads)		
Weight	7.9 kg		
Mounting	Optional wall-mount bracket		
Power Supply			
DC Input	DC 24 input (Molex DC-in jack)		
AC Input	450W (24V/18.75A) AC/DC Medical grade adapter		
Environmental			
Operating Temperature	0°C to 40°C		
Storage Temperature	-20°C to 70°C		
Humidity	5% to 95%, non-condensing		
Vibration	Operating vibration: 2Grms, 5-500Hz, 3 axes, Package (NON-OP) vibration: 3.44Grms, 10-1000Hz, 3 axes (W/MXM, W/SSD)		
EMC	EN55032/35, CE, FCC		
Safety	UL/cUL and CB (62368-1:2014)		
Medical Grade	Compliant with IEC 60601-1:2005+A1:2012+A2:2020(3.2edition)/IEC60601-1-2:2014+A1:2020(4.1edition)		